


## LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 165.06 lm/W			
MODEL	80H4 110	Imax(cd)	5473	S/MH(C0/180)	1.55
NOMINAL POWER(W)	80	LOR(%)	100.0	S/MH(C90/270)	1.54
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	13205	$\eta$ UP,DN(C0-180)	0.0,50.5
NOMINAL FLUX(lm)	13200	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,49.5
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	220.1	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	5052	5027	5014	4998	5071	5015	4972	4952	0- 10	477.8	477.8	3.62,3.62
20	5010	5027	5060	5030	5081	5003	4950	4907	10- 20	1416	1894	14.3,14.3
30	5088	5207	5332	5301	5348	5218	5100	4997	20- 30	2347	4241	32.1,32.1
40	5144	5170	5150	5175	5235	5168	5051	5043	30- 40	3301	7542	57.1,57.1
50	3541	3487	3492	3480	3545	3429	3419	3452	40- 50	3433	10975	83.1,83.1
60	430.9	526.3	584.2	589.2	498.4	455.9	451.7	475.3	50- 60	1721	12696	96.1,96.2
70	166.5	211.4	194.6	205.9	189.4	192.9	175.2	197.6	60- 70	305.2	13001	98.5,98.5
80	75.57	95.36	100.4	97.95	76.39	96.13	96.44	93.32	70- 80	140.3	13141	99.5,99.6
90	10.72	30.31	38.59	35.66	11.89	35.87	39.23	35.27	80- 90	64.06	13205	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 9343.8 lm

%lum = 70.8%

%lamp = 70.8%

Conical surface Flux(120deg): 12696 lm

%lum = 96.1%


%lamp = 96.2%

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	12375	23708
80	12953	17210
75	11189	14858
70	14492	16935
65	18101	22808
60	25650	34773
55	95992	106559
50	163932	161667
45	193527	190420

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## WEC AND CCEC

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.240	.136	.043	.233	.133	.042	.220	.126	.040	.208	.120	.039	.197	.114	.037		
2.0	.234	.128	.039	.228	.126	.039	.217	.121	.038	.207	.116	.036	.197	.112	.035		
3.0	.224	.119	.036	.219	.117	.035	.209	.114	.035	.200	.110	.034	.192	.106	.033		
4.0	.213	.111	.033	.209	.109	.032	.200	.106	.032	.192	.103	.031	.185	.100	.031		
5.0	.202	.103	.030	.198	.102	.030	.190	.099	.029	.183	.097	.029	.177	.094	.028		
6.0	.191	.096	.027	.188	.095	.027	.181	.093	.027	.175	.091	.027	.169	.089	.026		
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.083	.025		
8.0	.172	.084	.024	.169	.083	.023	.163	.081	.023	.158	.080	.023	.153	.079	.023		
9.0	.163	.079	.022	.160	.078	.022	.155	.077	.022	.150	.075	.022	.146	.074	.021		
10.0	.154	.074	.021	.152	.073	.020	.147	.072	.020	.143	.071	.020	.139	.070	.020		

ρcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.176	.157	.140	.150	.135	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016		
2.0	.165	.132	.105	.141	.114	.091	.097	.079	.063	.056	.046	.037	.018	.015	.012		
3.0	.156	.114	.081	.134	.098	.070	.092	.068	.049	.053	.040	.029	.017	.013	.009		
4.0	.148	.100	.064	.127	.087	.055	.087	.060	.039	.051	.035	.023	.016	.012	.008		
5.0	.141	.089	.051	.121	.077	.045	.084	.054	.032	.048	.032	.019	.016	.010	.006		
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.046	.029	.016	.015	.009	.005		
7.0	.129	.074	.036	.111	.064	.031	.077	.045	.022	.044	.026	.013	.014	.009	.004		
8.0	.123	.068	.031	.106	.059	.027	.073	.042	.019	.043	.025	.011	.014	.008	.004		
9.0	.118	.063	.027	.102	.055	.023	.070	.039	.016	.041	.023	.010	.013	.007	.003		
10.0	.113	.059	.023	.097	.051	.020	.067	.036	.015	.039	.021	.009	.013	.007	.003		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

NAME: LED LIGHT					TYPE:					WEIGHT:				
SPEC.:					DIM.:					SERIAL No.:				
MFR.:					SUR.:21cm*16cm					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.9	21.2	20.1	21.4	21.6	19.9	21.3	20.2	21.5	21.6				
3H	19.7	21.0	20.0	21.2	21.4	19.8	21.0	20.1	21.2	21.5				
4H	19.7	20.8	20.0	21.1	21.3	19.7	20.9	20.0	21.1	21.4				
6H	19.6	20.7	19.9	20.9	21.2	19.7	20.7	20.0	21.0	21.3				
8H	19.6	20.6	19.9	20.9	21.1	19.6	20.7	20.0	21.0	21.2				
12H	19.5	20.5	19.9	20.8	21.1	19.6	20.6	20.0	20.9	21.2				
4H 2H	19.7	20.9	20.0	21.1	21.4	19.8	20.9	20.1	21.2	21.4				
3H	19.6	20.6	20.0	20.9	21.2	19.7	20.7	20.0	21.0	21.2				
4H	19.6	20.5	19.9	20.8	21.1	19.6	20.5	20.0	20.8	21.2				
6H	19.5	20.3	19.9	20.7	21.0	19.6	20.4	20.0	20.7	21.1				
8H	19.5	20.2	19.9	20.6	21.0	19.6	20.3	20.0	20.7	21.1				
12H	19.5	20.1	19.9	20.5	20.9	19.6	20.3	20.0	20.6	21.0				
8H 4H	19.5	20.2	19.9	20.6	20.9	19.5	20.3	19.9	20.6	21.0				
6H	19.5	20.1	19.9	20.5	20.9	19.5	20.1	20.0	20.5	20.9				
8H	19.5	20.0	19.9	20.4	20.9	19.5	20.1	20.0	20.5	20.9				
12H	19.5	19.9	19.9	20.4	20.8	19.6	20.0	20.1	20.5	20.9				
12H 4H	19.4	20.1	19.9	20.5	20.9	19.5	20.2	19.9	20.5	20.9				
6H	19.4	20.0	19.9	20.4	20.8	19.5	20.0	20.0	20.4	20.9				
8H	19.5	19.9	19.9	20.3	20.8	19.5	20.0	20.0	20.4	20.9				
Variations with the observer position at spacings:														
S = 1.0H	+ 1.8 / - 2.9					+ 1.6 / - 2.3								
1.5H	+ 0.9 / - 1.6					+ 0.8 / - 1.5								
2.0H	+ 3.6 / - 7.1					+ 3.4 / - 6.7								

CIE Pub.117, 13200 lm Total Lamp Luminous Flux Correct ( $8\log(F/F_0) = 9.0$ )

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT)    k(RI) x RCR = 5									
k = 0.60	64	53	47	63	53	47	62	52	47	41
0.80	75	65	58	74	64	58	72	64	58	52
1.00	84	75	69	83	74	68	81	75	68	62
1.25	91	83	77	90	82	76	87	81	76	70
1.50	96	88	82	94	87	82	91	85	81	74
2.00	101	95	90	100	94	89	97	92	88	81
2.50	104	98	93	102	97	93	99	94	91	83
3.00	107	101	97	105	100	96	101	97	94	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	105	102	104	102	99	91
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004										
Suspended										
SHRNOM = 1.25										

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

ISOCANDELA DIAGRAM

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### AAI Figure

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

Flux out:11976 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:



## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:



